


## CMX7045

### Marine AIS-SART Processor

(Automatic Identification System—Search and Rescue Transmitter)

PP7045/1 November 2011



48-pin VQFN

48-pin LQFP

#### Market Overview

AIS-SART (Automatic Identification System—Search and Rescue Transmitter) is a self-contained unit used to locate a survival craft, life raft, distressed vessel or person by sending updated position reports using standard AIS position reports.


The specification for the AIS-SART has been developed by the IEC (International Electrical Committee), TC80 AIS Work Group.

The AIS-SART was added to the GMDSS regulations, effective January 2010. The international standard is IEC 61097-14.

AIS-SART derives position and time synchronisation from a built-in GNSS receiver and transmits its position with an update rate of 1 minute. Eight identical position reports are sent each minute to maintain a high probability that at least one of the position reports is sent on the highest point of a wave.

Long battery life is a critical requirement, units must have a long standby battery life and be ready to operate in a distress situation for a long period of time.

AIS-SARTs are typically cylindrical, brightly coloured and can also be incorporated into life jackets.



#### CMX7045 Brief Description

The CMX7045 is a dedicated processor for marine Automatic Identification System-Search and Rescue Transmitter (AIS-SART) operation, fully meeting the requirements of the IEC 61097-14 international standard.

This highly-integrated and flexible device includes a 9600 baud GMSK modulator for transmission of formatted data. Additional auxiliary functions are also provided to further support the system host, these include: a two-input 10-bit ADC, four 10-bit DACs, two system clock outputs and four GPIOs.


The CMX7045 offers low-power sleep modes to ensure maximum system battery life and is available in a small 48-pin LQFP or VQFN package.

#### Features

- Tx AIS 9600bps GMSK modulator
- AIS burst frame formatting
  - Bit stuffing
  - NRZI coding
  - Training sequence insertion
  - CRC generation
  - AIS slot Tx buffer
- Flexible Tx interface
- Conforms to IEC 61097-14
- Battery monitor function
- Configured by Function Image™
- Auxiliary functions
  - Two clock generators
  - Two 10-bit ADCs
  - Four 10-bit DACs
- Active integration roadmap
- Low-power 3V-3.6V operation
- Small, low profile 48-pin LQFP and VQFN

#### Key Benefits

- Equipment – fast time to market
- Off-the-shelf solution
- Reduced development time
- Field proven operation and performance
- Only requires small, low-cost host micro
- High integration solution
- Includes many sub-systems that reduce the overall system size and cost:
  - PA ramp automation
  - ADC for battery monitor
  - Integrated AIS modem with Tx burst frame formatting
- Built on FirmASIC® technology
- Evaluation kit and support available
- Roadmap to high quantity, low cost
- Maximum support



## General Description

The AIS system uses two basic channel access mechanisms: Self Organising Time Division Multiple Access (SOTDMA) and Carrier-Sensing Time Division Multiple Access (CSTDMA). The CMX7045 is compatible with both systems and offers additional features which simplify the implementation of an AIS-SART device conforming to international standard IEC 61097-14.

The CMX7045 is built on *FirmASIC*® technology. The Function Image™ (FI) file, which defines the operational capabilities of the device, may be obtained from the CML Technical Portal, following registration. This is in the form of a 'C' header file which can be included into the host controller software. The FI data file is no greater than 24kbytes.

### Tx Modem Functions


- AIS 25kHz channel
  - (GMSK, 9600bps, 2.4kHz deviation, BT = 0.4)
- AIS Burst mode with full AIS frame formatting (HDLC-type)
  - Bit stuffing
  - NRZI coding
  - Training sequence and start/stop flag insertion
  - CRC generation
- AIS Raw mode (for greater flexibility)
- Supports arbitrary data streams for user-defined protocols
- 160-byte (equivalent to 5 AIS slots) Tx data buffer
- Flexible Tx Interface
- Two-point modulation outputs, with independent gain and polarity controls

### Analogue I/O Functions

- Auxiliary ADC system
  - A two-input 10-bit successive approximation ADC with integrated sample and hold
- Auxiliary DAC system
  - Four general-purpose auxiliary 10-bit DACs
  - Ramping auxiliary DAC (using DAC 1)
    - DAC steps through a user-configured sequence of DAC output values to develop a specific rising/falling DAC output signal. This is useful for ramping an RF PA, and can be configured to operate automatically at the start and end of a burst.


### System Functions

- All internal sub-systems are controlled via a single serial host interface to reduce host  $\mu$ C pin count and simplify external host driver complexity
- Transaction oriented command/response logical host interface executes tasks, supporting normal operation, device configuration, and functions to assist manufacturing calibration trimming of external circuits
- Internal system clock derived from reference oscillator and eliminates the need for additional XTAL or baseband clock oscillator
- Auxiliary clock synthesisers generate two clocks for external use to support peripheral devices
- Function Image™ is loaded directly from the host  $\mu$ C via C-BUS
- Integrated 2.5V regulator can develop 2.5V from required 3.3V supply
- Powersave facilities minimise total system power.



Function Block Diagram

## Pin-out and External Components




Components	
R1	100k
R2	220k
R3	100k
R4	100k
C1	18pF
C2	18pF
C3	10nF
C7	100nF
C8	100pF
C9	100pF
C17	10μF
C18	10nF
C19	10nF
C20	10μF
C21	10nF
C22	10nF
C23	10nF
C24	10μF
X1	9.6MHz


## Evaluation Support

The CMX7045 can be evaluated with the PE0402 CMX704x series evaluation kit. Interfacing to a PC can be achieved with our PE0002 universal interface card with GUI and scripts available to assist product evaluation.

Alternatively any microcontroller evaluation/emulator kit can be used to drive the CMX7045's serial bus.




## Package Options



Mechanical Outline for 48-pin LQFP Package (L4)

Order as CMX7045L4



Mechanical Outline for 48-pad VQFN Package (Q3)

Order as CMX7045Q3

## Electrical Specification Summary

Operating Limits	Min.	Max.	Unit
Supply Voltage:			
$DV_{DD} - DV_{SS}$	3.0	3.6	V
$AV_{DD} - AV_{SS}$	3.0	3.6	V
$V_{DEC} - DV_{SS}$	2.25	2.75	V
Operating Temperature	-40	+85	°C
Clock Frequency	9.6	19.2	MHz
Function Image™ size		24	kBytes

DC Parameter - Supply Current	Min.	Typ.	Max.	Unit
<b>All Powersaved (Deep Sleep mode)</b>				
$DI_{DD}$ ( $DV_{DD} = 3.3V$ , $V_{DEC} = 2.5V$ )	–	24	100	µA
$AI_{DD}$ ( $AV_{DD} = 3.3V$ )	–	4	20	µA
<b>Tx Mode</b>				
$DI_{DD}$ ( $DV_{DD} = 3.3V$ , $V_{DEC} = 2.5V$ )	–	20	–	mA
$AI_{DD}$ ( $AV_{DD} = 3.3V$ )	–	11	–	mA

Transmit Parameters	Min.	Typ.	Max.	Unit
<b>AIS (GMSK 9600bps), 25kHz channel</b>				
Bit rate accuracy	–	–	±50	ppm
BT	–	0.4	–	
Storage time (filter delay)	–	8	–	bits
Tx Buffer size	–	–	176	Bytes
SLOT CLOCK Rise/Fall time	–	–	1.0	µs

Comprehensive technical datasheet and support material is available from the CML website.

Click here to link to the [CML website](#) or search for: CMX7045



CML's proprietary *FirmASIC*® component technology reduces cost, time to market and development risk, with increased flexibility for the designer and end application. *FirmASIC*® combines Analogue, Digital, Firmware and Memory technologies in a single silicon platform that can be focused to deliver the right feature mix, performance and price for a target application family. Specific functions of a *FirmASIC*® device are determined by uploading its Function Image™ during device initialization. New Function Images™ may be later provided to supplement and enhance device functions, expanding or modifying end-product features without the need for expensive and time-consuming design changes. *FirmASIC*® devices provide significant time to market and commercial benefits over Custom ASIC, Structured ASIC, FPGA and DSP solutions. They may also be exclusively customised where security or intellectual property issues prevent the use of Application Specific Standard Products (ASSP's).

	 <b>CML Microcircuits (UK) Ltd</b> <small>COMMUNICATION SEMICONDUCTORS</small>	 <b>CML Microcircuits (USA) Inc.</b> <small>COMMUNICATION SEMICONDUCTORS</small>	 <b>CML Microcircuits (Singapore) Pte Ltd</b> <small>COMMUNICATION SEMICONDUCTORS</small>
Phone:	+44 (0) 1621 875500	+1 336 744 5050 800 638 5577	+65 62 888129
Fax:	+44 (0) 1621 875600	+1 336 638 5577	+65 62 888230
Email Sales:	Sales@cmlmicro.com	us.sales@cmlmicro.com	sg.sales@cmlmicro.com
Email Tech Support:	techsupport@cmlmicro.com	us.techsupport@cmlmicro.com	sg.techsupport@cmlmicro.com
<div> <a href="http://www.cmlmicro.com">www.cmlmicro.com</a> </div> <div>           Search for: <b>cmlmicro</b> </div>			